

Underlayment Options

Shaw offers a complete series of quality underlayment options that will accommodate any installation requirement. All options are for use over concrete or wood substrates on all grades of approved subflooring. Shaw SilentStep 3-in-1 and Shaw 2-in-1 provide a moisture barrier to protect your floor.



- Superior performance acoustical flooring underlayment with unsurpassed sound absorption properties
- Impact Insulation Class (IIC) rating of 72dB
- Sound Transmission Class (STC) rating of 72dB
- Attached polyethylene moisture barrier
- Seam overlap protection with peel and stick adhesive strip eliminating the need to tape seams when installing over concrete
- Superior foam density
- 100% closed cell polyolefin foam core
- Thickness .08" (2mm)
- Standard roll size 40" x 30' (100 sq. ft.)



- "Just right" thickness for comfort and stability
- Closed cell foam construction
- Bonded polyethylene layer provides a moisture retardant barrier to protect your floor
- Aids in sound absorption
- Provides support for installation system
- For use over concrete or wood substrates on all grade levels
- Does not support the growth of molds and mildews
- Roll size 100 sq. ft.



- Proper thickness for comfort and stability
- For use on or above grade level over wood substrate
- Provides support for installation system
- Aids in sound absorption
- Does not support the growth of molds and mildews
- Roll size 100 sq. ft.



shawfloors.com